



HI ROAD ST

The Hi Road ST is an ST tire designed for towed trailer applications. With its radial construction, the Hi Road ST is engineered to deliver long life and superior towing stability.

TIRE FEATURES

- Radial construction provides strength and durability
- Tread is designed to reduce excessive heat build up
- Tread pattern delivers a stable and quiet ride
- Rubber compound engineered to provide low rolling resistance
- Nylon overlay on 15" and 16" sizes.



Tire size	LI/SR	PLY	T.D. 32nds	O.D. in.	S.W. in.	R.W. in.	LCC (1x) lbs@psi	LCC (2x) lbs@psi
ST175/80R13	91/87L	6	10	24.0	7.0	5.00	1355@50	1200@50
ST185/80R13	94/89L	6	10	24.6	7.2	5.00	1475@50	1280@50
ST205/75R14	100/96L	6	10	26.1	8.0	5.50	1760@50	1565@50
ST215/75R14	102/98L	6	10	26.7	8.5	6.00	1870@50	1650@50
ST205/75R15	107/102L	8	10	27.1	8.0	5.50	2150@65	1870@65
ST225/75R15	117/112L	10	10	28.3	8.8	6.00	2830@80	2470@80
ST235/80R16	124/120L	10	10	30.7	9.2	6.50	3520@80	3080@80
ST235/85R16	125/121L	10	10	31.7	9.2	6.50	3640@80	3200@80

