




# TRAIL CLIMBER AT02



Size	PART#	LI/SR	L.R.	T.D.	OD	SW	RW	UTQG	MAX LOAD	MAX LOAD
				32nds	in.	in.	in.		lbs@psi (1X)	lbs@psi (2X)
235/75R15	20898	109S	XL	13	28.86	9.25	6	620 A B	2271@50	
235/70R16	20899	106S		13	28.98	9.45	7	620 A B	2094@44	
245/75R16	20900	111S		13	30.47	9.76	7	620 A B	2403@44	
265/70R16	20901	112T		13	30.63	10.71	8	620 A B	2469@44	
265/75R16	20902	116S		13	31.65	10.51	8	620 A B	2756@44	
235/65R17	20903	104S		13	29.06	9.45	7	620 A B	1984@44	
245/65R17	20904	107S		13	29.53	9.76	7	620 A B	2149@44	
245/70R17	20905	110T		13	30.55	9.76	7	620 A B	2337@44	
255/65R17	20906	110T		13	30.08	10.24	8	620 A B	2337@44	
265/65R17	20907	112S		13	30.55	10.71	8	620 A B	2469@44	
265/70R17	20908	115S		13	31.65	10.71	8	620 A B	2679@44	
265/65R18	20909	114T		13	31.54	10.71	8	620 A B	2601@44	
265/70R18	20910	116T		13	32.64	10.71	8	620 A B	2756@44	
275/65R18	20911	116T		13	32.09	10.98	8	620 A B	2756@44	
275/55R20	20897	117T	XL	13	31.89	11.18	9	620 A B	2833@50	
265/50R20	20912	111T	XL	13	30.47	10.91	9	620 A B	2403@50	
275/60R20	20913	115T		13	32.99	10.98	8	620 A B	2679@44	
285/45R22	20914	114H	XL	13	32.09	11.22	10	620 A B	2601@50	
LT225/75R16	20921	115/112S	10PR	16	29.29	8.78	6		2680@80	2470@80
LT235/85R16	20922	120/116S	10PR	16	31.73	9.25	7		3042@80	2778@80
LT245/75R16	20923	120/116S	10PR	16	30.47	9.76	7		3042@80	2778@80
LT265/75R16	20924	123/120S	10PR	16	31.65	10.51	8		3415@80	3085@80
LT235/80R17	20925	120/117R	10PR	16	31.81	9.25	7		3085@80	2835@80
LT245/70R17	20926	119/116S	10PR	16	30.55	9.76	7		3000@80	2755@80
LT245/75R17	20927	121/118S	10PR	16	31.5	9.76	7		3195@80	2910@80
LT265/70R17	20928	123/120S	10PR	16	31.65	10.71	8		3415@80	3085@80
LT285/70R17	20929	126/123S	10PR	16	32.76	11.5	9		3750@80	3415@80
LT315/70R17	TBD	126/123S	10PR	16	34.41	12.72	10		3750@65	3415@65
LT265/70R18	20931	124/121S	10PR	16	32.64	10.71	8		3525@80	3195@80
LT275/65R18	20932	123/120R	10PR	16	32.09	10.98	8		3415@80	3085@80
LT275/70R18	20933	125/122R	10PR	16	33.19	10.98	8		3640@80	3305@80
LT265/60R20	20934	121/118R	10PR	16	32.52	10.71	8		3195@80	2910@80
LT275/55R20	20935	120/117R	10PR	16	31.89	11.18	9		3085@80	2835@80
LT275/60R20	20936	123/120R	10PR	16	32.99	10.98	8		3415@80	3085@80
LT275/65R20	20937	126/123R	10PR	16	34.09	10.98	8		3750@80	3415@80
LT285/60R20	20938	125/122R	10PR	16	33.46	11.5	9		3640@80	3305@80
LT305/55R20	20939	121/118R	10PR	16	33.23	12.44	10		3195@65	2910@65
31X10.50R15	20915	109S	6PR	16	30.51	10.55	9		2270@50	
35X12.50R17	TBD	125R	10PR	16	34.53	12.52	10		3640@65	
33X12.50R18	20917	118S	10PR	16	32.52	12.52	10		2910@65	
35X12.50R18	20918	123R	10PR	16	34.53	12.52	10		3415@65	
33X12.50R20	20919	114S	10PR	16	32.52	12.52	10		2600@65	
35X12.50R20	20920	121R	10PR	16	34.53	12.52	10		3195@65	



The Summit Trail Climber AT02 is your trusted all terrain tire for trucks and SUVs. The AT02 is just as at home on the trails as it is navigating the daily roads and highways. Reliable in all seasons, with deep tread and proudly wearing the 3PMS certification badge. Enjoy the Trail Climber AT02, as it ensures a smooth and quiet ride every time.

### TIRE FEATURES

- Wide tread footprint, supported by reinforced shoulders, ensure even pressure distribution sustaining even wear for extended tread life.
- Functional scalloped shoulders with deep tread depths and enhanced sidewall biters guarantees ample traction when required
- Four circumferential grooves with lateral shoulder channels expedite water evacuation.

50,000 Mile Limited Treadwear Warranty  
R, S AND T SPEED RATED UTQG 620 A B

